



POLYTONE™ SYNTHETIC RESINS Modified Maleic Resins

TECHNICAL DATA

POLYTONE™ M 131

Chemical Classification	Rosin Modified Maleic Resin
Type	Oil Soluble
Physical Form	Broken Lumps
Colour	Yellow to light brown
Melting Point (Capillary)	125° C – 135 ° C
Viscosity of 50% solution in Toluene at 30° C by B 4 Ford Cup	30 - 40 sec
Acid Value	20 mg KOH/ g resin (Max)

Application POLYTONE™ M 131 is used in Varnishes, Paints and Over Print Varnishes, N.C. Lacquers etc.

Solubility POLYTONE™ M 131 is soluble Mineral Turpentine Oil and Toluene

Packaging Available in 25 Kg bags

Shelf Life Store under cool dry conditions. It is recommended that the material be used within 12 months from the date of manufacture

P&P/TDS/POLYTONE™ M-131/REV001/21.12.2011
Copyright©2011 Polyols & Polymers Pvt.Ltd.

• POLYOLS & POLYMERS PVT.LTD. ☒ C-1/58-59, GIDC, VAPI, GJ, INDIA ☎ info@polyolsandpolymers.net 🌐 www.polyolsandpolymers.net •

The information contained herein is to the best of our knowledge, accurate and reliable. The information given herein is for reference only and is subjected to change without prior notice. However, as use conditions are not within our control no guarantees are given or are to be inferred, nor is freedom from any patent to be inferred.

POLYTONE™ is a trademark of Polyols & Polymers Pvt.Ltd. • ISO 9001:2008 Certified